



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : B41F 7/30, 33/00</p>	A1	<p>(11) International Publication Number: WO 00/32397</p> <p>(43) International Publication Date: 8 June 2000 (08.06.00)</p>		
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; padding: 5px;"> <p>(21) International Application Number: PCT/SE99/02172</p> <p>(22) International Filing Date: 24 November 1999 (24.11.99)</p> <p>(30) Priority Data: 9804187-4 2 December 1998 (02.12.98) SE</p> <p>(71) Applicant (for all designated States except US): JIMEK AB [SE/SE]; Box 14, S-232 01 Arlööv (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): HANSSON, Birger [SE/SE]; Nils Pers väg 5, S-232 51 Åkarp (SE).</p> <p>(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, Box 4188, S-203 13 Malmö (SE).</p> </td> <td style="width: 50%; vertical-align: top; padding: 5px;"> <p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p> </td> </tr> </table>			<p>(21) International Application Number: PCT/SE99/02172</p> <p>(22) International Filing Date: 24 November 1999 (24.11.99)</p> <p>(30) Priority Data: 9804187-4 2 December 1998 (02.12.98) SE</p> <p>(71) Applicant (for all designated States except US): JIMEK AB [SE/SE]; Box 14, S-232 01 Arlööv (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): HANSSON, Birger [SE/SE]; Nils Pers väg 5, S-232 51 Åkarp (SE).</p> <p>(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, Box 4188, S-203 13 Malmö (SE).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(21) International Application Number: PCT/SE99/02172</p> <p>(22) International Filing Date: 24 November 1999 (24.11.99)</p> <p>(30) Priority Data: 9804187-4 2 December 1998 (02.12.98) SE</p> <p>(71) Applicant (for all designated States except US): JIMEK AB [SE/SE]; Box 14, S-232 01 Arlööv (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): HANSSON, Birger [SE/SE]; Nils Pers väg 5, S-232 51 Åkarp (SE).</p> <p>(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, Box 4188, S-203 13 Malmö (SE).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>			
<p>(54) Title: A METHOD AND DEVICE AT A SPRAYING RAMP FOR A PRINTING PRESS</p> <div style="text-align: center; margin: 20px 0;"> </div>				
<p>(57) Abstract</p> <p>In a method for controlling the spraying of fountain solution in a printing press by means of electrically controlled spray valves (2) in a spray ramp (1), the current profile – at the supply of electric pulses to the solenoid of each valve (2) – from the solenoid is fed back to a valve controlling microcontroller (5) for providing an indication of the functionality of the valve.</p>				

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A METHOD AND DEVICE AT A SPRAYING RAMP FOR A PRINTING PRESS

5

Technical Field

The present invention relates to a method and device for controlling the spraying of fountain solution in a printing press by means of electrically controlled spray valves in a spray ramp.

Background of the Invention

As is well known in the art, a spray dampening device in the form of a spray ramp provided with electrically controlled spray valves is used in a printing press for spraying fountain solution on a rotating roller for transfer to a printing plate.

The spray ramp with its valves may be delivered from one source, whereas the control means for the valves may be delivered from another source and combined with the spray ramp at the mounting in a printing press. This means that certain factors of importance for the spray result may not be taken into account.

It may be more advantageous for the customer to buy from a single source an integrated spray process, including the spray ramp with its valves, with an internal feedback of parameters or properties of importance for the spray result, so that the spraying is fully controlled.

The Invention

This may according to the invention be attained in that at the supply of electric pulses to the solenoid of each valve the current profile from the solenoid is fed back to a valve controlling microcontroller for providing an indication of the functionality of the valve. This feedback can be used for diagnosis, for correction and/or for alarm. It provides an important possibility for preventive maintenance and can minimize the number of undesired stops.

Also, the physical properties of the fountain solution fed to the valves can be sensed and supplied to a microcontroller having individual output conduits to the valves and a communication receiver with on/off
5 information, so that an integrated spray process is created.

Normally, the temperature, pressure, and flow of the fountain solution are sensed, as these properties are most influential for the spray result.

10 **Brief Description of the Drawing**

The invention will be described in further detail below under reference to the accompanying drawing, in which Fig 1 is a general representation of a first embodiment of the invention at a spray ramp, Fig 2 corresponds to Fig 1
15 but shows a second embodiment of the invention, Fig 3 is an illustration of a sensor portion to be used at the invention, and Fig 4 graphically illustrates a current signal, a movement of a spray valve plunger induced hereby, and a spray flow profile created by said movement,
20 respectively.

Detailed Description of Embodiments

A spray ramp 1 for a printing press is shown in Figs 1 and 2. The design and function of such a spray ramp is well known in the art, and the ramp is not described in
25 detail herein. Spray valves 2 in the ramp 1 are fed with so called fountain solution through a pipe 3, and the spraying of the fountain solution through the valves is governed by a solenoid controlled plunger in each valve.

Each solenoid is electrically operated through a
30 conduit 4. The current for operating the solenoid may have the appearance of line a) in Fig 4, i.e. a square wave (slightly modified - not shown - with triggering spikes at the ends), where the pulses for opening the valve may have a typical duration of 5 ms and the zero current periods may
35 have a typical duration of 8 ms. The resulting movements of

the valve plunger may have the appearance of line b) in Fig 4, and the spray flow profile from the valves 2 may then be as illustrated by line c) in Fig 4. The normal spray flow profile is thus a series of spray pulses with very short
5 duration, which provides the desired spray result on the roller of the printing press where the ramp is mounted. Each valve 2 is individually controlled, as indicated by the presence in Fig 1 of four conduits 4.

The individual current signal through the conduit 4
10 is created in a microcontroller 5 having a voltage supply 6 (for example 24 V) and a communication receiver 7 with on/off information for externally activating the microprocessor-based controller 5.

The microcontroller 5 has a sensor portion 5' (also
15 depicted in Fig 3), in which there are sensors 8, 9, 10 for sensing the temperature, pressure, and flow, respectively, of the fountain solution in the pipe 3. These values are internally fed into the microprocessor of the controller 5 as important control parameters for providing appropriate
20 spray flow profiles for the valves for accomplishing the desired spraying (evenness, distribution, amount, and so on) on the roller in the printing press.

Each microcontroller 5 can in a practical case have eight output conduits 4. Two ramps 1 with four valves 2
25 each or one ramp with eight valves may thus be controlled.

As a modification of the embodiment shown in Fig 1, the sensor portion 5' may be arranged in the ramp 1. The sensors 8, 9, 10 are in this case externally connected to the controller 5.

30 In a second embodiment according to Fig 2, which may be preferred if a self-contained ramp unit is desired, the entire microcontroller with its sensor portion may be arranged inside the ramp 1 in close proximity to the valves 2. Here, the fountain solution pipe 3, the voltage supply
35 6, and the communication receiver 7 extend into the ramp 1.

An important feature of the microcontroller 5 is the possibility to obtain a feedback regarding the functionality of the plunger in relation to its solenoid in each valve in response to the supplied current profile. The
5 current to the solenoid may for example be measured over a resistor and fed back to the microcontroller 5. If this measured profile differs too much from a preset profile window, it may be taken as an indication of a malfunction. The current profile may be used for diagnosing the function
10 of each valve, so that measures may be taken in time to prevent undesired stops. Alternatively, individual corrections of the current may be made for restoring the function of a valve. Also, an alarm may be triggered at a current profile falling outside given limits. In other
15 words, the working cycle for a valve may be analysed.

CLAIMS

1. A method for controlling the spraying of fountain solution in a printing press by means of electrically controlled spray valves (2) in a spray ramp (1), c h a r -
5 a c t e r i z e d in that physical properties of the fountain solution fed to the valves (2) are sensed and supplied to a microcontroller (5) having individual output conduits (4) to the valves and a communication receiver (7) with on/off information, so that an integrated spray
10 process is created.

2. A method according to claim 1, c h a r a c t e r -
i z e d in that the temperature, pressure, and flow of the fountain solution are sensed.

3. A method according to claim 1, c h a r a c t e r -
15 i z e d in that the current profile from the solenoid of each valve (2) is fed back to the microcontroller (5) for providing an indication of the functionality of the valve.

4. A device for controlling the spraying of fountain solution in a printing press by means of electrically
20 controlled spray valves (2) in a spray ramp (1), c h a r - a c t e r i z e d by a microcontroller (5) having individual output conduits (4) to the valves (2) and a communication receiver (7) with on/off information and by means (5', 8, 9, 10) for sensing physical properties of the
25 fountain solution fed to the valves and supplying them to the microcontroller.

5. A device according to claim 4, c h a r a c t e r -
i z e d in that said means is a sensor portion (5'), through which the fountain solution is supplied and which
30 is provided with sensors (8, 9, 10) for temperature, pressure, and flow.

6. A device according to claim 5, c h a r a c t e r -
i z e d in that the sensor portion (5') is arranged in conjunction with the microcontroller (5).

7. A device according to claim 5, c h a r a c t e r-
i z e d in that the sensor portion (5') is arranged in the
spray ramp (1).

8. A device according to claim 5, c h a r a c t e r-
5 i z e d in that both the microcontroller (5) and the
sensor portion (5') are arranged in the ramp (1).

1/1






Fig. 4



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/02172

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B41F 7/30, B41F 33/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B41F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0257195 A2 (SMITH R.P.M. CORPORATION), 2 March 1988 (02.03.88) --	1-8
A	EP 0325381 A2 (JIMEK AB), 26 July 1989 (26.07.89) --	1-8
A	EP 0341384 A2 (ROCKWELL INTERNATIONAL CORPORATION), 15 November 1989 (15.11.89) --	1-8
A	WO 9113760 A1 (BERNTSSON, R.), 19 Sept 1991 (19.09.91) --	1-8

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 March 2000

Date of mailing of the international search report

22-03-2000

Name and mailing address of the ISA
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Åke Olofsson / MR
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/02172

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9510414 A1 (GRAFISKI TEAM AB), 20 April 1995 (20.04.95) --	1-8
A	US 4469024 A (M.A. SCHWARTZ ET AL), 4 Sept 1984 (04.09.84) --	1-8
A	US 4708058 A (G.R. SMITH), 24 November 1987 (24.11.87) --	1-8
A	US 5038681 A (S. HULTBERG), 13 August 1991 (13.08.91) -- -----	1-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/SE 99/02172

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
EP	0257195	A2	02/03/88	JP	63072549 A	02/04/88
				US	4708058 A	24/11/87
EP	0325381	A2	26/07/89	SE	0325381 T3	
				AU	2856289 A	20/07/89
				CA	1313388 A	02/02/93
				DE	68924433 D,T	09/05/96
				JP	2006863 A	11/01/90
				JP	2746975 B	06/05/98
				NZ	227640 A	26/02/91
				NZ	234310 A	26/02/91
				US	5038681 A	13/08/91
				US	4873925 A	17/10/89
EP	0341384	A2	15/11/89	SE	0341384 T3	
				AU	614593 B	05/09/91
				AU	641774 B	30/09/93
				AU	3240089 A	09/11/89
				AU	7932691 A	12/09/91
				CA	1303899 A	23/06/92
				DE	68926762 D,T	14/11/96
				JP	2059345 A	28/02/90
				US	4899653 A	13/02/90
WO	9113760	A1	19/09/91	AT	129184 T	15/11/95
				AU	7495391 A	10/10/91
				CA	2077649 A	07/09/91
				DE	69024974 D,T	30/05/96
				DE	69114021 D,T	15/05/96
				EP	0502946 A,B	16/09/92
				EP	0572391 A,B	08/12/93
				ES	2080303 T	01/02/96
				JP	5505153 T	05/08/93
				RU	2049294 C	27/11/95
				SE	465764 B,C	28/10/91
				SE	9000780 A	07/09/91
				US	5293753 A	15/03/94
WO	9510414	A1	20/04/95	DE	69417250 D,T	04/11/99
				EP	0725732 A,B	14/08/96
				SE	506715 C	02/02/98
				SE	9303368 A	12/04/95
				US	5673622 A	07/10/97
US	4469024	A	04/09/84	NONE		
US	4708058	A	24/11/87	EP	0257195 A	02/03/88
				JP	63072549 A	02/04/88

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/12/99

International application No.

PCT/SE 99/02172

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5038681 A	13/08/91	AU 2856289 A	20/07/89
		CA 1313388 A	02/02/93
		DE 68924433 D,T	09/05/96
		EP 0325381 A,B	26/07/89
		SE 0325381 T3	
		JP 2006863 A	11/01/90
		JP 2746975 B	06/05/98
		NZ 227640 A	26/02/91
		NZ 234310 A	26/02/91
<hr/>			